



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Anton LED Pendant ANP Series

Features

This modern double layer drum design provides a dramatic look and features Lumafuse™ laminated fabric/acrylic shade in 2 colors. White bottom acrylic diffuser disperses the light. Suspended with a 3 ft. adjustable rigid stem expandable up to 9 ft.

Construction

Metal housing and canopy. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Black or Satin Nickel finish.

Diffuser

Utilizing Lumafuse™ laminated fabric to acrylic in Jute or Linen White. Matte white acrylic bottom diffuser.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
18W = 1400 source lumens
30W = 2400 source lumens
42W = 3200 source lumens
60W = 5400 source lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs., 90 CRI

Certification

All fixtures are cETLus listed for indoor damp locations.
*Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

**Specifications and dimensions
subject to change without notice.**

Ordering Information:

Satin Nickel/Jute	Satin Nickel/ Linen White*	LED	Source Lumens	Adjustable CCT	DIA.	H
ANP1214LAJUDSN-JT	ANP1214LAJUDSN-LW	18W	1400	3000K/3500K/4000K	12-1/4"	4-3/4"
ANP1524LAJUDSN-JT	ANP1524LAJUDSN-LW	30W	2400	3000K/3500K/4000K	15"	5-1/2"
ANP1932LAJUDSN-JT	ANP1932LAJUDSN-LW	42W	3200	3000K/3500K/4000K	19-1/4"	5-1/2"
ANP2432L5AJUDSN-JT	ANP2432L5AJUDSN-LW	42W	3200	3000K/3500K/4000K	24"	7-1/2"
ANP3044L5AJUDSN-JT	ANP3044L5AJUDSN-LW	60W	5400	3000K/3500K/4000K	30"	9-1/2"

Black/Jute	Black/Linen White*	LED	Source Lumens	Adjustable CCT	DIA.	H
ANP1214LAJUDBK-JT	ANP1214LAJUDBK-LW	18W	1400	3000K/3500K/4000K	12-1/4"	4-3/4"
ANP1524LAJUDBK-JT	ANP1524LAJUDBK-LW	30W	2400	3000K/3500K/4000K	15"	5-1/2"
ANP1932LAJUDBK-JT	ANP1932LAJUDBK-LW	42W	3200	3000K/3500K/4000K	19-1/4"	5-1/2"
ANP2432L5AJUDBK-JT	ANP2432L5AJUDBK-LW	42W	3200	3000K/3500K/4000K	24"	7-1/2"
ANP3044L5AJUDBK-JT	ANP3044L5AJUDBK-LW	60W	5400	3000K/3500K/4000K	30"	9-1/2"



SN-LW



SN-JT

